



VENSKA

solidline

EXTERIOR DOORS










In order to give our customers product with good quality parametres and good price relation we are focused on operational excellence and production flexibility.



Solid - term that encompasses key values we strongly promote in our work: reliability, durability and trustworthiness. Underlined, give our brand a new meaning of Solidline.



TECHNICAL DATA

- standard door thickness **60mm**
- standard frame **92mm** or 105mm as not standard feature
- thermal insulation characteristics **U=0,85-0,98**
- door frame reinforced with plywood
- special waterproof fiberboard (HDF) on the surface
- aluminium plate 0,4/0,5mm in the middle
- thermal insulation EPS
- additional moisture barrier at the bottom part of the door
- 2-layer surface treatment on each side
- 3 adjustable security hinges
- **aluminium+oak 25mm** threshold
- standard NCS color S 0502-Y both sides
- outward opening
- standard center unit 8765 included

All doors available in standard sizes:

880 x 1980mm

880 x 2080mm

980 x 1980mm

980 x 2080mm

Non-standard sizes available on individual request.

VENSKA

Y406



Y401



Y403



Y502



Y505



Y501



Y506



Y512



Y100



Y107



Y102



Y106



Y108



Y101



Y508



Y500



Y513



Y509



Y203



Y208



Y212



Y213



Y217



Y202



Y215



Y214



Y216



Y201



Y515



Y503



Y515



Y200

